

Friction Savers

Available in 3 lengths | 23kN rating | Multi layered webbing



- 23KN product rating
- Meets ANSI Z133 н. standard



				SMALL RING		LARGE RING		
	ITEM #	LENGTH	RING TYPE	ID	OD	ID	OD	MSRP
	NAFS-24	24 in (61 cm)	Aluminum (Shown)	28 mm	52 mm	45 mm	70 mm	\$44.95
	NAFS-36	36 in (91 cm)						\$47.95
	NAFS-48	48 in (122 cm)						\$49.95
	NSFS-24	24 in (61cm)	Steel	29 mm	58 mm	48 mm	77 mm	\$44.95
	NSFS-36	36 in (91 cm)						\$47.95
	NSFS-48	48 in (122 cm)						\$49.95

HTS#: 5806.32.2000 Country of Origin =Taiwan



- **FEATURES &** BENEFITS
- Aids in reducing friction during ascend
- Suitable for use as a false crotch
- Prevents tree damage
- Available with rated forged steel or aluminum friction rings
- 3 lengths: 24", 36", 48"
- Constructed from multi layered, fray resistant, custom Nylon webbing
- Bright coloration for ease of visibility
- Dense, multi layered webbing weave resists twisting
- Colored coded ends for ease of retrieval