

TRIPOD An ISO 9001 : 2015 Certified Company

Ref: SF-TP-800 & SF-TP-800 (DP)

VIRAJ Tripod has been designed for confined space entry / retrieval applications. Its simplistic design allows the easy set up providing the user a means of controlled ascent and descent in minimal time

FEATURES

- For 7 ft. : Range 1.40 mtr. (4.6 ft.) to 2.13 mtr. (7 ft.)
- For 10 ft. : Range 2.0 mtr. (6.56 ft.) to 3.0 mtr. (10 ft.)
- A pulley system provided for steel cable guiding in case a which is used in the system.
- Securely connected two eye bolts to be used for connection to personal protective equipment.
- Two pulley system provided to pass the wire rope of winch mounted on the leg and retrieval block on the other leg simultaneously.

HOW TO USE

- Refer User Instruction

LOAD CAPACITY

Maximum Load Capacity

- 500 kgf

MATERIAL

- Tripod Legs : Material Alluminium Allow
Finish Anodized
- Cast Head : Material Alluminium Allow
Finish Powder Coated
- Eye Bolt & Locking Pins : Material Stainless Steel Finish
Polished

WEIGHT

- SF-TP-800 (7FT) : 13 KG \pm 0.200 kg.
- SF-TP-800 (10FT) : 15 KG \pm 0.200 kg.

RELEVANT STANDARDS

- 23 KN

RELEVANT STANDARDS

- Meets or EN 795 CLASS B



C-36 UPSIDC Industrial Area, Rooma,
Kanpur- 209402 (UP) INDIA



Tripod Single Pulley Head

Ref: SF-TP-800



Tripod Double Pulley Head

Ref: SF-TP-800



LENGTH	SPECIFICATION	COMPLIANCE
7 ft.	<ul style="list-style-type: none"> Fully adjustable telescopic legs, adjustable height from 1.15m to 2.15m. Wheelbase (Footprint) : 1.5m Diameter. Weight : 13 kg appx. Maximum load capacity : 500 kgf. 	EN 795 CLASSB
10 ft.	<ul style="list-style-type: none"> Fully adjustable telescopic legs, adjustable height from 1.5m to 2.2m. Wheelbase (Footprint) : 1.8m Diameter. Weight : 15 kg appx. Maximum load capacity : 500 kgf. 	



info@virajsyntax.com



www.virajsyntax.com